| | | REV | DATE | REVISION | N RECORD | DWN | AUTH |
|--|--|---|-----------------|-----------------------------|----------------------------------|-----------------|---------------|
| INPUT | Connectors | - | 04-12-12 | Initial Release | | PAC | |
| Frequency | RF Input/Output: SMA(f) | | | | | | |
| 10 MHz | Power, Monitoring: Feed Thru Terminals | | | | | | |
| Level | GND: Ground Turret | | | | | | |
| | | | | | | | |
| +13 dBm ±1 dB into 50 ohms | Packaging | | | | Connections | | |
| OUTPUT | Nickel-plated machined | | | | | | |
| Frequency | aluminum housing – J3PM | | | | iction | | |
| 10.24 GHz | Mounting | | | | ply Voltage und, Case | | |
| Level | Threaded inserts on base, | | | | Output | | |
| +13 dBm \pm 2 dB into 50 ohms | 6 places, #2-56 | | | | se Lock Voltage se Lock Alarm | | |
| STABILITY | POWER REQUIREMENTS | | | | ernal Reference Input | | |
| Aging (free-running) | Warm-Up Power | | | | | | |
| 1 x 10 ⁻⁶ first year | ≤ 21 Watts for 5 minutes | | | | | | |
| after 30 days operating, typical | Total Power | 1.00 | <u></u> | $\sim \sim \sim \sim$ | | | 2 |
| | ≤ 17.5 Watts at +25°C | 0.75 — 7 | | | | Ş | |
| 5 x 10 ⁻⁷ second year, typical | Supply Voltage | 0.44 — | | z © | | 4 | |
| 3 x 10 ⁻⁷ per year thereafter, typical | +15 VDC ±5% | 0 | | | | | _ |
| Phase Noise L(f), typical, (free-running) | ADJUSTMENT | | | | | | |
| 100 Hz -87 dBc/Hz | Loop BW | 0 | 0.55 | 1.33 1.64 2.40 | | 5.76 | 5.31 |
| 1 KHz -112 dBc/Hz | Target Bandwidth: ~200 Hz | | | | | | |
| 10 KHz -129 dBc/Hz | Type 2 Loop | 4.00 — | ب ہکتر | <u>hh</u> | | | |
| 100 KHz -130 dBc/Hz | CRYSTAL | 3.915 | × | | | | <u> </u> |
| Temperature Stability | | | | | | | |
| $\pm 5 \times 10^{-7}$ free-running from 0 to $\pm 50^{\circ}$ C | Type | | | | | | |
| | 80 MHz SC-cut (x128) | | | | | | |
| (Ref. +25°C) | OTHER | | | | | | |
| Harmonics | Label | | | | | | |
| -25 dBc | Use conventional label with the | | | | | | |
| Sub-Harmonics | following information: | 2.000 — 🔿 | | | | | 0 |
| -60 dBc | 501-25770 (Current Rev.) | | | | | | |
| PLL Reference Products | 10.24 GHz MXO-PLM | | | | | | |
| -60 dBc | +15 VDC | | | | | | |
| Spurious | Serial # - Date Code | | | | | | |
| -80 dBc, excluding power | (Mark connectors with function) | | Threaded | 43 Ff | | | |
| supply line related spurs | Test Data | | 6 places, 0 | nserts, #2-56, 190" deep | | | |
| Phase Lock Alarm | - Output Level | 0.085 – | < | | | | 6 |
| TTL | - Phase Noise – free-running | 0 — 🖉 | ` | | | | |
| Locked: +3.5 VDC to +5.2 VDC (Hi) | - Harmonics, Subs, Products, Spurious | 0 | 3 | | | | 6.225 6.31 |
| Out-of-Lock: +0.8 VDC max (Lo) | - Power – Warm-up and Total | c | 5 | | | | 9.0 |
| Phase Lock Voltage Monitor | rower wann ap and rotar | | | | | | |
| Voltage monitor pin supplied | | Wenzel Associates, Inc. | | | | | |
| MECHANICAL | | Austin, Texas | | | | | |
| Dimensions | | Title: | | | | | |
| 6.31 x 4 x 1" | | 10.24 GHz Multiplied Crystal Oscillator (MXO-PLM) | | | | | |
| | | P/N: | | Rev: Date: | Drawn: | - Ref: | - |
| | | | 1-25770 | - 04-12 | | | |
| | | | | _ | | | |
| | | Tolerances (except as | noted) | | X Dec: FSCM: | Page 1 o | £2 |
| | | Dimension | s are in inches | ±0.030" ±0 | .010" 62821 | raye I O | · ~ |
| | | | | | | | |