

OUTPUTS

Output	Frequency	Level (into 50Ω)
A	100 MHz	+13 ±2 dBm
B	500 MHz	+16 ±2 dBm

STABILITY

Aging

- 1 x 10⁻⁶ first year
- after 30 days operating, typical
- 5 x 10⁻⁷ second year, typical
- 3 x 10⁻⁷ per year thereafter, typical

Phase Noise L(f), dBc/Hz, typical

	100 MHz	500 MHz
10 Hz	-100	-85
100 Hz	-130	-120
1 kHz	-158	-146
10 kHz	-175	-167
100 kHz	-176	-170

Temperature Stability

±5 x 10⁻⁷, 0 to +50°C (Ref. +25°C)

Harmonics

≤ -25 dBc

Sub-Harmonics

≤ -60 dBc

Spurious

≤ -80 dBc, excluding power
supply line related spurs

MECHANICAL

Dimensions

3.25 x 4 x 1"

Connectors

RF Outputs: SMA(f)
Power, ET: Feed Thru Terminals
GND: Ground Turret

Packaging

Nickel-plated machined
aluminum housing – G1-01

Mounting

Threaded inserts on base,
#2-56, 6 places

POWER REQUIREMENTS

Warm-Up Power

≤ 14.5 Watts for 5 minutes

Total Power

≤ 10.5 Watts at +25°C

Supply Voltage

+15 VDC ±5%

ADJUSTMENT

Mechanical Tuning

±4 x 10⁻⁶

Electrical Tuning

±5 x 10⁻⁷, ±5 VDC
Negative Slope

CRYSTAL

Type

100 MHz SC-cut (x5)

OTHER

Label

Use conventional label with the
following information:

501-26838 (Current Rev.)

100M/500M GMXO-FR

+15 VDC


Serial # - Date Code

(Mark connectors with function)

Test Data

- Output Level
- Phase Noise
- Temperature Stability
- Harmonics, Subs, Spurious
- Power – Warm-up and Total

REV	DATE	REVISION RECORD	DWN	AUTH
-	05-17-13	Initial Release	PAC/L	
A	02-06-14	Output Level to +16 dBm	PAC	
Mod	03-07-16	Added 100 MHz ULN output	CB	



Wenzel Associates, Inc.

Austin, Texas

Title:

**100 MHz & 500 MHz Golden
Multiplied Crystal Oscillator (GMXO-FR)**

P/N:

501-26838

Rev:

A_M

Date:

03-07-17

Drawn:

62821

Ref:

Tolerances:
(except as noted)
Dimensions are in inches

0.XX Dec:
±0.030"

0.XXX Dec:
±0.010"

FSCM:
62821

Page 1 of 1