

OUTPUT

Frequency

700 MHz

Level

+16 dBm ± 2 dB into 50 ohms

STABILITY

Aging

1×10^{-6} first year

after 30 days operating, typical

5×10^{-7} second year, typical

3×10^{-7} per year thereafter, typical

Phase Noise L(f)

100 Hz -119 dBc/Hz

1 KHz -145 dBc/Hz

10 KHz -165 dBc/Hz

100 KHz -167 dBc/Hz

Temperature Stability

$\pm 5 \times 10^{-7}$, 0° to +50°C (Ref +25°C)

Harmonics

≤ -25 dBc

Sub-Harmonics

≤ -60 dBc

Spurious

≤ -80 dBc, excluding power
supply line related spurs

MECHANICAL

Dimensions

3.25 x 4 x 1"

Connectors

SMA(f) and solder pins on side

Packaging

Nickel-plated machined
aluminum housing – G1

Mounting

Threaded inserts on base,
#2-56, 6 places

POWER REQUIREMENTS

Warm-Up Power

≤ 14 Watts for 5 minutes

Total Power

≤ 8 Watts at +25°C

Supply Voltage

+15 VDC $\pm 5\%$

ADJUSTMENT

Mechanical Tuning

$\pm 4 \times 10^{-6}$

Electrical Tuning

$\pm 5 \times 10^{-7}$, ± 5 VDC

Negative slope

CRYSTAL

Type

100 MHz SC-cut (x7)

OTHER

Label

Use conventional label with the
following information:

501-27305 (Current Rev.)

700 MHz GMXO-FR

+15 VDC

Serial # - Date Code

(Mark connectors with function)

Test Data

Output Level

Phase Noise


Temperature Stability

Harmonics, Subs, Spurious

Power – Warm-up and Total

Tuning – MT and ET

REV	DATE	REVISION RECORD	DWN	AUTH
-	11-01-13	Initial Release	Liz	
A	02-06-14	Output Level to +16 dBm	PAC	



Wenzel Associates, Inc.

Austin, Texas

Title:

700 MHz Multiplied Crystal Oscillator, Golden

P/N:

501-27305

Rev:

A

Date:

02-06-14

Drawn:

Ref:

Tolerances:
(except as noted)
Dimensions are in inches

0.XX Dec:

± 0.030 "

0.XXX Dec:

± 0.010 "

FSCM:

62821

Page **1** of **1**