

INPUT

Frequency

10 MHz

Level

+13 dBm ± 1 dB into 50 ohms

OUTPUT

Frequency

3.6 GHz

Level

+13 dBm ± 2 dB into 50 ohms

STABILITY

Aging (free-running)

1×10^{-6} first year

after 30 days operating, typical

5×10^{-7} second year, typical

3×10^{-7} per year thereafter, typical

Phase Noise L(f), typical, (free-running)

100 Hz -106 dBc/Hz

1 KHz -131 dBc/Hz

10 KHz -148 dBc/Hz

100 KHz -149 dBc/Hz

Temperature Stability

$\pm 5 \times 10^{-7}$ free-running from 0 to +50°C
(Ref. +25°C)

Harmonics

-25 dBc

Sub-Harmonics

-60 dBc

PLL Reference Products

-60 dBc

Spurious

-80 dBc, excluding power
supply line related spurs

MECHANICAL

Dimensions

7.31 x 4 x 1"

Connectors

RF Input/Output: SMA(f)

Power, Monitoring: Feed Thru Terminals

GND: Ground Turret

Packaging

Nickel-plated machined
aluminum housing – G3PM

Mounting

Threaded inserts on base,
6 places, #2-56

POWER REQUIREMENTS

Warm-Up Power

≤ 24.5 Watts for 5 minutes

Total Power

≤ 20 Watts at +25°C

Supply Voltage

+15 VDC $\pm 5\%$

ADJUSTMENT

Loop BW

Target Bandwidth: ~200 Hz

Type 2 Loop

PHASE LOCK STATUS

Phase Lock Alarm

TTL

Locked: +3.5 VDC to +5.2 VDC (Hi)

Out-of-Lock: +0.8 VDC max (Lo)

Phase Lock Voltage Monitor

Voltage monitor pin supplied

CRYSTAL

Type

100 MHz SC-cut (x36)

OTHER

Label

Use conventional label with the
following information:

501-29217 (Current Rev.)

3.6 GHz GMXO-PLM

+15 VDC

Serial # - Date Code

(Mark connectors with function)

Test Data

- Output Level


- Phase Noise – free-running

- Harmonics, Subs, Products, Spurious

- Power – Warm-up and Total

REV	DATE	REVISION RECORD	DWN	AUTH
-	07-07-15	Initial Release	CB	

G3PM MXO Connections	
Connector	Function
1	Supply Voltage
2	Ground, Case
4	RF Output
5	Phase Lock Voltage
6	Phase Lock Alarm
7	External Reference Input



Wenzel Associates, Inc.

Austin, Texas

Title:

3.6 GHz Multiplied Crystal Oscillator (GMXO-PLM)

P/N:

501-29217

Rev:

-

Date:

07-07-15

Drawn:

Ref:

Tolerances:
(except as noted)
Dimensions are in inches

0.XX Dec:
 ± 0.030 "

0.XXX Dec:
 ± 0.010 "

FSCM:
62821

Page 1 of 1