INPUT
Frequency
5 MHz
Level
+13 dBm ±1 dB into 50 ohms OUTPUT
Frequency
10.5 GHz
Level
+13 dBm ±2 dB into 50 ohms
STABILITY
Aging (free-running)
1 x 10 <sup>-6</sup> first year
after 30 days operating, typical
5 x 10 <sup>-7</sup> second year, typical 3 x 10 <sup>-7</sup> per year thereafter, typical
3 x 10 ' per year thereafter, typical
Phase Noise L(f), typical, (free-running)
100 Hz -77 dBc/Hz
1 KHz        -105 dBc/Hz 10 KHz       -129 dBc/Hz
100 KHz -130 dBc/Hz
Temperature Stability ±5 x 10 <sup>-7</sup> free-running from 0 to +50°C
±5 x 10 ' free-running from 0 to +50°C
(Ref. +25°C)
Harmonics
-25 dBc
Sub-Harmonics
-60 dBc PLL Reference Products
-60 dBc Spurious
-80 dBc, excluding power
supply line related spurs
Phase Lock Alarm
TTL
Locked: +3.5 VDC to +5.2 VDC (Hi)
Out-of-Lock: +0.8 VDC max (Lo)
Phase Lock Voltage Monitor
Voltage monitor pin supplied
MECHANICAL
Dimensions
6.31 x 4 x 1"

### Connectors

RF Input/Output: SMA(f)

Power, Monitoring: Feed Thru Terminals

**GND: Ground Turret** 

## **Packaging**

Nickel-plated machined aluminum housing – J3PM

### Mounting

Threaded inserts on base,

6 places, #2-56

## **POWER REQUIREMENTS**

Warm-Up Power

≤ 21 Watts for 5 minutes

### **Total Power**

≤ 17 Watts at +25°C

# **Supply Voltage**

+15 VDC ±10%

#### **ADJUSTMENT**

## Loop BW

Target Bandwidth: <300 Hz

Type 2 Loop

#### CRYSTAL

### **Type**

105 MHz SC-cut (x100)

# **OTHER**

## Label

Use conventional label with the

following information:

501-29521 (Current Rev.)

10.5 GHz MXO-PLM

+15 VDC

Serial # - Date Code

(Mark connectors with function)

#### **Test Data**

- Output Level
- Phase Noise free-running
- Harmonics, Subs, Products, Spurious
- Power Warm-up and Total

REV	DATE	REVISION RECORD	DWN	AUTH
-	10-30-15	Initial Release	CB	
Α	03-10-16	Voltage to ± 10%	CB	

J3PM MXO Connections			
Connector	Function		
1 2 4	Supply Voltage Ground, Case RF Output		
5	Phase Lock Voltage		
6	Phase Lock Alarm		
7	External Reference Input		



