OUTPUT Frequency 80 MHz Level +13 dBm ±2 dB into 50 ohms **STABILITY** Aging 1×10^{-6} per year after 30 days operating, typical Phase Noise L(f), Static 100 Hz -132 dBc/Hz 1 kHz -160 dBc/Hz 10 kHz -176 dBc/Hz 100 kHz -176 dBc/Hz Phase Noise L(f), Dynamic, typical 10 Hz -72 dBc/Hz 50 Hz -73 dBc/Hz 100 Hz -100 dBc/Hz 300 Hz -120 dBc/Hz 1 kHz -142 dBc/Hz -154 dBc/Hz 2 kHz **Temperature Stability** $\pm 2 \times 10^{-7}$. 0° to +50°C (Ref +25°C) Harmonics ≤ -30 dBc Spurious ≤ -90 dBc, excluding power supply line related spurs **MECHANICAL** Dimensions 2.8" x 3.0" x 1.15" Connectors SMA(f) and solder pins on side Packaging Nickel-plated machined aluminum case - (CVI-1) POWER REQUIREMENTS Warm-Up Power \leq 7 Watts for 5 minutes **Total Power** ≤ 4 Watts at +25°C Supply Voltage +15 VDC ±5%

ADJUSTMENT Mechanical Tuning $+4 \times 10^{-6}$ **Electrical Tuning** ±5 x 10⁻⁷ min, ±5 VDC Negative slope CRYSTAL Type 80 MHz SC-cut (low-g) **Acceleration Sensitivity** $\leq 3 \times 10^{-10}$ /g per axis, typical **ENVIRONMENTAL Operating Temperature** 0° to +50°C Storage Temperature -40° to +85°C Vibration Level $0.01 \text{ g}^2/\text{Hz}$ 10 Hz to 2 kHz Resonance (Internal Mount Natural Frequency) ~50 Hz, typical OTHER Label Use conventional label with the following information: 501-29545 (Current Rev.) 80 MHz Citrine +15 VDC Serial # - Date Code **Test Data** Output Level Phase Noise, Static and Dynamic Temperature Stability Harmonics, Spurious Power - Warm-up and Total Tuning – MT and ET

