INPUT
Frequency
10 MHz
Level
+7 dBm ±6 dB into 50 ohms
OUTPUT
Frequency
2.7 GHz
Level
+13 dBm ± 2 dB into 50 ohms
STABILITY
Aging (free-running)
1 x 10 ⁻⁶ first year
after 30 days operating typical
5 x 10 ⁻⁷ second year, typical
3 x 10 ⁻⁷ per year thereafter, typical
Phase Noise L(f), typical, (free-running)
100 Hz -98 dBc/Hz
1 KHz -124 dBc/Hz
10 KHz -141 dBc/Hz
100 KHz -142 dBc/Hz
Temperature Stability
±5 x 10 ⁻⁷ free-running from 0 to +50°C
(Ref. +25°C)
Harmonics
-25 dBc
Sub-Harmonics
-60 dBc
PLL Divider Products
-60 dBc
Spurious
-80 dBc, excluding power
supply line related spurs
Phase Lock Alarm
TTL
Locked: +3.5 VDC to +5.2 VDC (Hi)
Out-of-Lock: +0.8 VDC max (Lo)
Phase Lock Voltage Monitor
Voltage monitor pin supplied
MECHANICAL
Dimensions

4.40 x 4 x 1"

Connectors

RF Input/Output: SMA(f)

Power, Monitoring: Feed Thru Terminals

GND: Ground Turret

Packaging

Nickel-plated machined aluminum housing – J2P

Mounting

Threaded inserts on base,

#2-56, 6 places

POWER REQUIREMENTS

Warm-Up Power

≤ 15.5 Watts for 5 minutes

Total Power

≤ 12 Watts at +25°C

Supply Voltage

+15 VDC ±5%

ADJUSTMENT

Loop BW

Target Bandwidth: ≤ 10 Hz

Type 2 Loop

CRYSTAL

Type

100 MHz SC-cut (x27)

OTHER

Label

Use conventional label with the following information:

501-29876 (Current Rev.)

2.7 GHz MXO-PLD

+15 VDC

Serial # - Date Code

(Mark connectors with function)

Test Data

- Output Level
- Phase Noise free-running
- Temperature Stability free-running
- Harmonics, Subs, Products, Spurious
- Power Warm-up and Total

REV	DATE	REVISION RECORD	DWN	AUTH
-	03-22-16	Initial Release	CB	

J2P MXO Connections			
Connector	Connector Function		
1	Supply Voltage		
2	Ground, Case		
4	RF Output		
5 Phase Lock Voltage			
6	Phase Lock Alarm		
7	External Reference Input		

12D MVO Connection



