

OUTPUTS

Output	Frequency	Level (into 50Ω)
A	100 MHz	+16 ±2 dBm
B	2 GHz	+13 ±2 dBm

STABILITY

Aging

- 1 x 10⁻⁶ first year
- after 30 days operating, typical
- 5 x 10⁻⁷ second year, typical
- 3 x 10⁻⁷ per year thereafter, typical

Phase Noise L(f), dBc/Hz, typical

	100 MHz	2 GHz
10 Hz	-105	-76
100 Hz	-136	-107
1 kHz	-162	-133
10 kHz	-183	-154
100 kHz	-188	-157

Temperature Stability

±5 x 10⁻⁷, 0 to +50°C (Ref. +25°C)

Harmonics

≤ -25 dBc

Sub-Harmonics

≤ -60 dBc

Spurious

≤ -80 dBc, excluding power
supply line related spurs

MECHANICAL

Dimensions

4.21 x 4 x 1"

Connectors

RF Outputs: SMA(f)
Power, ET: Feed Thru Terminals
GND: Ground Turret

Packaging

Nickel-plated machined
aluminum housing – G2-03

Mounting

Threaded inserts on base,
#2-56, 6 places

POWER REQUIREMENTS

Warm-Up Power

≤ 17 Watts for 5 minutes

Total Power

≤ 13 Watts at +25°C

Supply Voltage

+15 VDC ±5%

ADJUSTMENT

Mechanical Tuning

±4 x 10⁻⁶

Electrical Tuning

±5 x 10⁻⁷, ±5 VDC

Negative Slope

CRYSTAL

Type

100 MHz SC-cut (x20)

OTHER

Label

Use conventional label with the
following information:

501-30244 (Current Rev.)

100M/2G GMXO-FR

+15 VDC


Serial # - Date Code

(Mark connectors with function)

Test Data

- Output Level
- Phase Noise
- Temperature Stability
- Harmonics, Subs, Spurious
- Power – Warm-up and Total

REV	DATE	REVISION RECORD	DWN	AUTH
-	08-09-16	Initial Release	CB	



Wenzel Associates, Inc.

Austin, Texas

Title:

**100 MHz & 2 GHz Golden
Multiplied Crystal Oscillator (GMXO-FR)**

P/N: 501-30244	Rev.: -	Date: 08-09-16	Drawn:	Ref:
--------------------------	-------------------	--------------------------	--------	------

Tolerances: (except as noted) Dimensions are in inches	0.XX Dec: ±0.030"	0.XXX Dec: ±0.010"	FSCM: 62821	Page 1 of 1
--	-----------------------------	------------------------------	-----------------------	-------------