

INPUT

Frequency

10 MHz

Level

+7 dBm \pm 6 dB into 50 ohms

OUTPUT

Frequency

2.8 GHz

Level

+13 dBm \pm 2 dB into 50 ohms

STABILITY

Aging (free-running)

1 x 10⁻⁶ first year

after 30 days operating, typical

5 x 10⁻⁷ second year, typical

3 x 10⁻⁷ per year thereafter, typical

Phase Noise L(f), typical, (free-running)

100 Hz -103 dBc/Hz

1 kHz -129 dBc/Hz

10 kHz -149 dBc/Hz

100 kHz -153 dBc/Hz

1 MHz -153 dBc/Hz

Temperature Stability

\pm 5 x 10⁻⁷ free-running from -20 to +70°C
(Ref. +25°C)

Harmonics

-25 dBc

Sub-Harmonics

-60 dBc

PLL Divider Products

-60 dBc

Spurious

-80 dBc, excluding power
supply line related spurs

MECHANICAL

Dimensions

5.4 x 4 x 1"

Connectors

RF Input/Output: SMA(f)

Power, Monitoring: Feed Thru Terminals

GND: Ground Turret

Packaging

Nickel-plated machined
aluminum housing – G2P

Mounting

Threaded inserts on base,
#2-56, 6 places

POWER REQUIREMENTS

Warm-Up Power

\leq 18.5 Watts for 5 minutes

Total Power

\leq 14.5 Watts at +25°C

Supply Voltage

+15 VDC \pm 5%

ADJUSTMENT

Loop BW

Target Bandwidth: \leq 60 Hz

Type 2 Loop

PHASE LOCK STATUS

Phase Lock Alarm

TTL

Locked: +3.5 VDC to +5.2 VDC (Hi)

Out-of-Lock: +0.8 VDC max (Lo)

Phase Lock Voltage Monitor

Electrical tuning monitor pin supplied

CRYSTAL

Type

112 MHz SC-cut (x25)

OTHER

Label

Use conventional label with the
following information:

501-30448 (Current Rev.)

2.8 GHz GMXO-PLD

+15 VDC

Serial # - Date Code

(Mark connectors with function)

Test Data

Output Level

Phase Noise (free-running)


Temperature Stability (free-running)

Harmonics, Subs, Products, Spurious

Power – Warm-up and Total

REV	DATE	REVISION RECORD	DWN	AUTH
-	11-01-16	Initial Release	CB	

G2P MXO Connections	
Connector	Function
1	Supply Voltage
2	Ground, Case
4	RF Output
5	Phase Lock Voltage
6	Phase Lock Alarm
7	External Reference Input



Wenzel Associates, Inc.

Austin, Texas

Title:

**2.8 GHz Golden Multiplied Crystal Oscillator
(GMXO-PLD)**

P/N:

501-30448

Rev:

-

Date:

11-01-16

Drawn:

62821

Ref:

Tolerances:
(except as noted)
Dimensions are in inches

0.XX Dec:
 \pm 0.030"

0.XXX Dec:
 \pm 0.010"

FSCM:
62821

Page 1 of 1