

## OUTPUT Frequency 8 GHz Level +13 dBm ±2 dB into 50 ohms **STABILITY** Aging $1 \times 10^{-6}$ first vear after 30 days operating, typical $5 \times 10^{-7}$ second year, typical $3 \times 10^{-7}$ per year thereafter, typical Phase Noise L(f), typical 10 Hz -57 dBc/Hz -88 dBc/Hz 100 Hz 1 KHz -115 dBc/Hz 10 KH z -132 dBc/Hz 100 KHz -133 dBc/Hz 1 MHz -150 dBc/Hz 10 MHz -152 dBc/Hz **Temperature Stability** ±5 x 10<sup>-7</sup>, 0° to +50°C (Ref +25°C) Harmonics ≤ -25 dBc Sub-Harmonics ≤ -60 dBc Spurious ≤ -80 dBc, excluding power supply line related spurs MECHANICAL Dimensions 4.16 x 4 x 1" Connectors SMA(f) and solder pins Packaging Nickel-plated machined aluminum housing – J3 Mounting Threaded inserts on base, #2-56, 6 places

## POWER REQUIREMENTS Warm-Up Power ≤ 13 Watts for 5 minutes **Total Power** ≤ 10 Watts at +25°C **Supply Voltage** +15 VDC ±5% ADJUSTMENT Mechanical Tuning $+4 \times 10^{-6}$ **Electrical Tuning** $\pm 5 \times 10^{-7}, \pm 5 \text{ VDC}$ Negative slope CRYSTAL Type 100 MHz SC-cut (x80) OTHER Label Use conventional label with the following information: 501-30596 (Current Rev.) 8 GHz GQMXO-FR +15 VDC Serial # - Date Code (Mark connectors with function) **Test Data** Output Level Phase Noise **Temperature Stability** Harmonics, Subs, Spurious Power - Warm-up and Total Tuning – MT and ET

| REV | DATE     | REVISION RECORD | DWN | AUTH |
|-----|----------|-----------------|-----|------|
| -   | 01-18-17 | Initial Release | PAC |      |
|     |          |                 |     |      |
|     |          |                 |     |      |
|     |          |                 |     |      |





| Austin, Texas  |                    |           |                       |                |               |  |  |  |  |
|--|--------------------|-----------|-----------------------|----------------|---------------|--|--|--|--|
| Title: 8 GHz Golden-Q Multiplied   Crystal Oscillator (GQMXO-FR) |                    |           |                       |                |               |  |  |  |  |
| <sup>P/N:</sup> 501-30596  | Rev:               | Date<br>0 | 1-18-17               | Drawn:         | Ref:<br>28134 |  |  |  |  |
| Tolerances:<br>(except as noted)<br>Dimensions are in inches     | 0.XX Dec:<br>±0.03 | 0"        | 0.XXX Dec:<br>±0.010" | FSCM:<br>62821 | Page 1 of 1   |  |  |  |  |