OUTPUT A (J2) Frequency 80 MHz Level +13 dBm ±2 dB into 50 ohms Phase Noise L(f), Static 100 Hz -130 dBc/Hz 1 kHz -158 dBc/Hz 10 kHz -173 dBc/Hz 100 kHz -174 dBc/Hz OUTPUT B (J1) Frequency 320 MHz Level +13 dBm ±2 dB into 50 ohms Phase Noise L(f), Static 100 Hz -118 dBc/Hz 1 kHz -143 dBc/Hz 10 kHz -159 dBc/Hz 100 kHz -160 dBc/Hz **STABILITY** Aging 1×10^{-6} first vear after 30 days operating, typical 5×10^{-7} second year, typical 3×10^{-7} per year thereafter, typical **Temperature Stability** ±5 x 10⁻⁷, 0° to +50°C (Ref +25°C) **Harmonics** ≤ -25 dBc Sub-Harmonics $\leq -50 \, \text{dBc}$ **Non-Harmonic Spurious** \leq -80 dBc, excluding power supply line related spurs **MECHANICAL** Dimensions 2" x 2" x 1.3" Connectors SMA(f) and solder pins on one side Packaging Nickel-plated machined aluminum housing (CVP-2A)

Mountina Threaded inserts, # 2-56, 4 places Tapped holes on sides, 16 places (provisions for shock mounts) POWER REQUIREMENTS Warm-Up Power ≤ 9 Watts for 5 minutes at +25°C **Total Power** ≤ 6 Watts at +25°C Supply Voltage +12 VDC ±5% ADJUSTMENT Mechanical Tuning ±4 x 10⁻⁶ **Electrical Tuning** $\pm 2 \times 10^{-7}$ min. ± 5 VDC Negative slope CRYSTAL Type 80 MHz SC-cut (x4) **Acceleration Sensitivity** $\leq 2 \times 10^{-10}$ /g per axis, typical **ENVIRONMENTAL Operating Temperature** 0° to +50°C Storage Temperature -40° to +85°C OTHER Label Use conventional label with the following information: 501-30626 (Current Rev.) 80/320 MHz Citrine +12 VDC Serial # - Date Code (Mark connectors with function) **Test Data** Output Level Phase Noise – Static Temperature Stability

Harmonics, Subs, Spurious

Power - Warm-up and Total

Tuning – MT and ET

