		REV	DATE	REVISION RECORD	DWN	AUTH
INPUT	Connectors	-	03-24-17	Initial Release	CB	
Frequency	RF Input/Output: SMA(f)					
10 MHz	Power, Monitoring: Feed Thru Terminals					
Level	GND: Ground Turret					
+13 dBm ±1 dB into 50 ohms	Packaging					
	Nickel-plated machined					
	aluminum housing – J2PM					
Frequency 980 MHz						
	Mounting			J2PM MXO Connectio	ns	
	Threaded inserts on base,			Connector Function		
+13 dBm ±2 dB into 50 ohms STABILITY	6 places, #2-56 POWER REQUIREMENTS			1 Supply Voltage 2 Ground, Case		
Aging (free-running)	Warm-Up Power			4 RF Output 5 Phase Lock Volta		
$1 \times 10^{-6}$ first year	≤ 14 Watts for 5 minutes			6 Phase Lock Alarr 7 External Referen		
after 30 days operating, typical	Total Power					
	≤ 10 Watts at +25°C		1.00 —			
$5 \times 10^{-7}$ second year, typical	Supply Voltage		0.75 — 7	0 <u>-0</u> čč ··	4	
$3 \times 10^{-7}$ per year thereafter, typical	+15 VDC ±5%		0.44 — 0.25 —	2 ©	<u>s</u>	
Phase Noise L(f), typical, (free-running)	ADJUSTMENT		0 —		<u>@~_</u>	
100 Hz -106 dBc/Hz	Loop BW		0	0.55 - 1.33 - 2.40 - 2.4	4.81 5.36	
1 KHz -133 dBc/Hz	Target Bandwidth: ~300 Hz				, Š	
10 KHz -150 dBc/Hz	Type 2 Loop		4.00 — 3.915 ∽ 🏳		<del>F_</del>	
100 KHz -151 dBc/Hz	CRYSTAL		3.915 -			
Temperature Stability	Туре					
±5 x 10 <sup>-7</sup> free-running from 0 to +50°C	70 MHz SC-cut (x14)					
(Ref. +25°C)	OTHER					
Harmonics	Label					
-25 dBc	Use conventional label with the		2.000 — 🖸	)	0	
Sub-Harmonics	following information:					
-60 dBc	501-30731 (Current Rev.)					
PLL Reference Products	980 MHz MXO-PLM					
-60 dBc	+15 VDC			Threaded Inserts, ∳2-56, 6 places, 0.190" deep		
Spurious	Serial # - Date Code		0.085 ¬	6 places, 0.190" deep		
<ul> <li>-80 dBc, excluding power</li> </ul>	(Mark connectors with function)			\	<u>م/</u> الح	
supply line related spurs	Test Data		0	2	5.270 5.36	
Phase Lock Alarm	- Output Level		c	5	<u>``</u> م	
TTL	- Phase Noise – free-running					
Locked: +3.5 VDC to +5.2 VDC (Hi)	- Harmonics, Subs, Products, Spurious					
Out-of-Lock: +0.8 VDC max (Lo)	<ul> <li>Power – Warm-up and Total</li> </ul>					
Phase Lock Voltage Monitor						
Voltage monitor pin supplied		Wenzel Associates, Inc.				
MECHANICAL		Title:				
Dimensions		980 MHz Multiplied Crystal Oscillator (MXO-PLM)				
5.36 x 4 x 1"		P/N: Rev: Date: Drawn: Ref:				
			1-30731	- 03-24-17		
		Tolerances		0.XX Dec: 0.XXX Dec:	FSCM:	
		(except as Dimension	noted) s are in inches	±0.030" ±0.010"	62821 Page 1	of <b>1</b>