OUTPUT
Frequency
160 MHz
Level
+13 dBm ±2 dB into 50 ohms
STABILITY
Aging
1 x 10 <sup>-6</sup> per year
after 30 days operating, typical Phase Noise L(f), Static
\ <i>\ \ \ \ \ \ \ \ \ \</i>
100 Hz -118 dBc/Hz
1 kHz -148 dBc/Hz
10 kHz -168 dBc/Hz
100 kHz -170 dBc/Hz
Temperature Stability
±5 x 10 <sup>-7</sup> , 0° to +50°C (Ref +25°C)
Harmonics
≤ -30 dBc
Spurious
≤ -90 dBc, excluding power
supply line related spurs
MECHANICAL
Dimensions
2 x 2 x 0.7"
Connectors
SMA(f) and solder pins on side
Packaging
Nickel-plated machined
aluminum case (CV-1A)
POWER REQUIREMENTS
Warm-Up Power
≤ 6 Watts for 5 minutes
Total Power
≤ 3 Watts at +25°C
Supply Voltage
+12 VDC ±5%
ADJUSTMENT
Mechanical Tuning
±4 x 10 <sup>-6</sup>
Electrical Tuning
±2 x 10 <sup>-7</sup> , ±5 VDC
Negative slope

CRYSTAL Type

OTHER Label

**Test Data** 

ENVIRONMENTAL Operating Temperature 0° to +50°C

Storage Temperature -40° to +85°C

following information: 501-31117 (Current Rev.)

Serial # - Date Code

Harmonics, Spurious Power – Warm-up and Total

Tuning – MT and ET

160 MHz Citrine +12 VDC


Output Level Phase Noise, Static Temperature Stability


160 MHz SC-Cut (low-g)
Acceleration Sensitivity


 $\leq$  5 x 10<sup>-10</sup>/g per axis, typical


Use conventional label with the


REV	DATE	REVISION RECORD	DWN	AUTH
-	08-15-17	Initial Release	PAC	











CV-1A					
Connector	Function				
P1 P2 P3 J1	Ground, Case Supply Voltage Electrical Tuning RF Output				

Connector numbers are for reference only and will not be marked on unit.



## Wenzel Associates, Inc.

Austin, Texas

Standard 160 MHz-SC Citrine Crystal Oscillator

P/N: 501-31117	Rev:	00 45 47		Drawn:		Ref: SPR
Tolerances: (except as noted) Dimensions are in inches	0.XX Dec: ±0.030"		0.XXX Dec: ±0.010"	FSCM: 62821	F	Page 1 of 1